


Raman Optical Fiber 125 µm

P/N: 36736



Overview

OFS Raman Fiber 125 µm is specifically designed for applications where a high Raman gain efficiency is required. The fiber is designed with a high index core and a small effective area which yields a high Raman gain efficiency.

With appropriate choice of pump wavelength, the Raman fiber can provide gain at any wavelength from 1100 to 1700 nm. Additionally, it offers bending performance, good splicing properties and low attenuation at the water peak.

Typical Applications

Discrete Broadband Raman Amplifiers Raman Lasers



Raman Optical Fiber 125 µm

P/N: 36736

Product Specifications	
Product Description	Raman Optical Fiber 125 µm
Physical Characteristics	
Cladding Diameter	125 ± 1.0 μm
Coating Diameter	200 ± 10 μm
Clad Non-Circularity	≤ 1.0%
Core Eccentricity	< 0.6 μm
Optical Characteristics	
Туре	Non-Standard
Cutoff Wavelength	≤ 1050 nm
Effective Area @ 1450 nm	$16.1 \pm 1.5 \mu m^2$
Effective Area @ 1550 nm	18.7 ± 1.5 µm²
Attenuation @ 1450 nm (Maximum)	0.46 dB/km
Attenuation @ 1550 nm (Maximum)	0.36 dB/km
Attenuation @ 1450 nm (Typical)	0.43 dB/km
Attenuation @ 1550 nm (Typical)	0.33 dB/km
Polarization Mode Dispersion (PMD) (Typical)	0.05 ps/km ^{0.5}
Polarization Mode Dispersion (PMD) (Maximum)	<0.5 ps/km ^{0.5}
PM or non-PM	Non-PM
Peak Raman Gain Efficiency (Typical)	2.5 (W·km)⁻¹
Mechanical and Environmental	
Operating Temperature	-40 to +85 °C
Proof Test Level	≥ 200 kpsi (1.38 GPa)
Order by Part Number	36736

For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.



Copyright © 2023 OFS Fitel, LLC. All rights reserved, printed in USA.

OFS Marketing Communications Date: 08/23





OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.