



A Furukawa Company

## Simplex 1000 $\mu\text{m}$ Step-Index 3.0 mm HCS<sup>®</sup> Fiber Optic Cable

P/N: AC01287-15



### Overview

OFS 3.0 mm HCS fiber cables are designed primarily for industrial data-communication applications. Taking advantage of the durability and toughness of HCS optical fibers, these tight-buffer cables surround the fiber with high-strength aramid yarn and are protected with a tough 3.0 mm diameter polyurethane jacket.

### Typical Applications

Corrosive Chemical  
Environments  
Hydrophone  
Repetitive Motion Applications  
Robotics  
Umbilicus Assemblies



A Furukawa Company

# Simplex 1000 µm Step-Index 3.0 mm HCS® Fiber Optic Cable

P/N: AC01287-15

Product Specifications	
Product Description	Simplex 1000 µm Step-Index 3.0 mm HCS Fiber Optic Cable
Physical Characteristics	
Construction	Simplex 1000
Numerical Aperture	0.37
Fiber Core Diameter	1000 ± 15 µm
Outer Cable Diameter	3 mm
Cable Weight	< 10 kg/km
Outer Jacket Material	Polyurethane
Outer Jacket Color	Orange
Flammability Rating	None
Crimp & Cleave Compatibility	SMA Connectors, ST Connectors
Optical Characteristics	
Type	Multimode Step-Index
Attenuation @ 850 nm	≤ 10 dB/km
Fiber Specifications	CF01493-15, 1000 µm HCS 0.37 NA Low OH Optical Fiber
Mechanical and Environmental	
Installation Load (Maximum)	125 lb. (555 N)
Operating Load (Maximum)	65 lb. (290 N)
Minimum Bend Installation	170 mm
Minimum Bend Operating	120 mm
Operating Temperature	-40 to +80 °C
Storage Temperature	-40 to +80 °C
Order by Part Number	<b>AC01287-15</b>
Product Description Code	HCP-M1000T-C01US

**OPTIONS:** Also available in breakout construction with up to 18 sub-units, jacket color, print legend, terminated assemblies

**NOTE:** The operating temperature ranges are general guidelines. Consult with our Technical Sales department to determine the optimal coating and jacketing material for your specific application. 1.860.678.6636.

**For additional information please contact your sales representative.**

You can also visit our website at [www.ofsoptics.com](http://www.ofsoptics.com) or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.



Copyright © 2019 OFS Fitel, LLC. All rights reserved, printed in USA.

OFS Marketing Communications  
Date: 12/19



HCS is a registered trademark of OFS Fitel, LLC. OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.